



TS250 SERIES INSTRUMENTS

INDUSTRIAL INSTRUMENT WITH ADVANCED FUNCTIONS



Versatile industrial desktop instruments for floor scale and chemical tank scale applications. Available in a NEMA 4X stainless steel or ABS enclosure.

THURMANSCALE.COM



CC# 15-099

MC# AM-6002



TS250 SERIES


INDUSTRIAL INSTRUMENT



The TS250 stainless steel enclosure meets general food and other industrial washdown requirements. It can be used in applications that require NEMA 4X rated weighing equipment.

For floor scale applications in dry environments, the TS250 ABS composite enclosure and mild steel Avenger® floor scale are recommended.

Thurman Scale's TS250 Series is an economically priced weight instrument with basic to advanced functionality and many customizable features. It is the perfect companion to Thurman's Avenger® floor scale and is highly reliable instrumentation for tank, vessel and hopper applications.



TS250 ABS Enclosure

Enclosure Types

- 304 Stainless Steel with NEMA 4X rating.
- ABS Plastic is heat, impact and chemical resistant.


Instrument Accessories

BATTERY POWER Five (5) "D" cell battery pack available for 304 Stainless NEMA 4X and ABS models.

4-20 mA MODULE The 4-20 mA Module provides an analog input for PLCs, data loggers or other controllers.

FIELD BUS INTERFACES Thurman offers popular fieldbus interfaces, such as DeviceNet, Profibus, ControlNet, Modbus TCP, Ethernet/IP and Ethernet/TCP to connect the TS250 Instrument to PLCs or PCs.

External DB9 output on ABS model



SS Battery Power Pack



ABS Battery Power Pack

Function Key Features

- 1 UNITS** — Five selectable units (lb, kg, oz, g, lb-oz) and one programmable custom unit. Units key also used with piece count and accumulation features.
- 2 ZERO** — Quickly zero off weight on the scale.
- 3 B/G / NET** — One-push selection from Gross weight to Net weight. Also used during accumulation and piece count operations and to set sleep timer.



1

2

3

4

5

6

Stainless steel
swivel bracket
(included with
all models)



4 **ON/OFF** — One touch to power instrument up or down.

5 **TARE** — Deducts container weight from the total weight.

6 **PRINT** — Custom or standard print formats. This key is also used to set clock format, time and date, and during Peak Hold operations.

TS250 CUSTOMIZATION

TS250 Series Instruments can be customized to meet your specific operational needs.

CUSTOM TICKET FORMAT

A distinct ticket format can be configured to allow the TS250 to print information that meets your requirements.

CUSTOM UNITS

Many applications are unique and require a unique unit of measure. The TS250 can accommodate these needs with this feature.

PROGRAMMABLE RS232 OUTPUT

The TS250 RS232 Output can be configured to provide serial data in a customer specified format.

MULTI-POINT CALIBRATION

The TS250's Multi-point Calibration function helps eliminate various linearity problems associated with platforms and tank applications.

ADVANCED FUNCTIONS



Easy-to-use piece counting function.

PIECE COUNTING

The TS250 has a standard piece counting feature that turns any scale into a basic counting scale. This feature minimizes the time it takes to count parts. See sample display above.

ACCUMULATION

This feature allows users to continuously store individual weight reading and count/total the readings whenever desired. It also minimizes or eliminates the time-consuming task of manually tracking weight.

STRESS TESTING

Certain manufacturers are required to *stress test* products. The TS250 is designed to easily accomplish this task. The unit captures the highest (or peak) weight reading and stores it. The printable reading remains stored until it is manually cleared or a higher peak weight is captured by the instrument.

Also known as Peak Hold, this feature provides stress test analysis that is required for ISO documentation.

TS250 SERIES INSTRUMENTS

INDUSTRIAL INSTRUMENT WITH ADVANCED FUNCTIONS

EXPERIENCE THE POWER OF THURMAN

IT'S THE SUPERIOR CHOICE

In addition to its broad line of vehicle scales and heavy capacity weighing equipment, Thurman Scale manufactures rugged and dependable products for customers with industrial weighing needs. Since 1819, Thurman has focused its efforts into building superior products and delivering complete customer satisfaction. That's why we believe you'll find Thurman to be the most valuable choice for all your weighing needs.


SPECIFICATIONS

Display	1.0" high, 6-digit, green backlit LCD
Enclosure	Black ABS plastic, NEMA 1 rated Stainless steel, NEMA 4X rated
Pushbutton Keys	Zero, Print, Units, Tare, On/Off, B/G Net
Units	lb, kg, oz, g, lb-oz or custom
Capacity	Selectable 0 to 999,999
Graduation Size	0.0001 to 50
Load Cells	Up to eight 350Ω cells or 16 1000Ω cells
Power Requirements	Choice of AC or AC/DC (requires 5 "D" cell batteries),

Battery life (backlight enabled)	One 350Ω load cell - 58 hours, Four 350Ω load cells - 33 hours
Mounting	Desk / Wall mount stand (all models)
Output	COM1 (standard): RS232, RS422, RS485 COM2 (standard): RS232, RS422, RS485 and 20 mA; External DB9 on ABS model
Remote switch inputs	Print, Tare, Gross/Net, Units, Zero
Accessories	4-20 mA module, ControlNet, Modbus TCP, Ethernet/IP, Ethernet/TCP, DeviceNet, Profibus
Approvals	NTEP CC# 15-099, MC #AM-6002, ETL


ABS PLASTIC ENCLOSURE

(Stainless steel bracket included — Battery power optional)



NEMA 4X STAINLESS STEEL ENCLOSURE

(Stainless steel bracket included — Battery power optional)



(800) 688-9741

Call between 8:00 a.m. – 5:00 p.m. Central Time
6800 W. 64th Street, Overland Park, Kansas 66202 • (614) 221-9077
Internet Address: <http://www.thurmanscale.com>

